#### Personal Protective Equipment

Safety



Protective



Half Face Respirator

# WHMIS Pictograms

# Not Controlled

**DOT Pictograms** 

# Not Regulated

#### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Loosefill Insulation Product Name: MSDS Manufacturer 23118-NAM

Number:

Synonyms:

PROPINK® Loosefill Fiber Glass Insulation, PROPINK

Complete  $^{\text{TM}}$  Blown-In Insulation, PROPINK  $\stackrel{\circ}{\otimes}$  L77 PINK Fiberglas  $^{\text{TM}}$  Insulation

Product Use/Restriction: Blowing Wool

Manufacturer Name: Owens Corning Insulating Systems, LLC

Address: One Owens Corning Parkway

Toledo, OH 43659

Customer Service Phone 1-800-GET-PINK or 1-800-438-7465 Number:

Health Issues Information: 1-419-248-8234 (8am-5pm ET) Technical Product 1-800-GET-PINK or 1-800-438-7465

Information:

Emergency Phone Number: 1-419-248-5330 (after 5pm ET and weekends)

CHEMTREC: 800-424-9300 (24 hours everyday)

(613) 996-6666 (Canada 24 hours everyday) Canutec:

Website: www.owenscorning.com MSDS Revision Date: August 12, 2010

WHMIS Class: Irritant



NFPA

**Chronic Health Effects** 

O

Х

Reactivity

Personal

Protection

### SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Fiber Glass (Wool)	65997-17-3	60 - 100 by weight
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	0 - 5 by weight

64741-88-4 0 - 5 by weight Non-Hazardous Statement: The remaining components of this product are non-hazardous or are in a small

enough quantity as to not meet regulatory thresholds for disclosure. These components contain no substances or impurities which would influence the

classification of this product.

# SECTION 3 - HAZARDS IDENTIFICATION

# **Applies to Product**

Emergency Overview: Exposure to dust may be irritating to eyes, nose, and throat.

Route of Exposure: Eye contact Skin contact

Inhalation

Potential Health Effects:

Skin:

Eye: May cause slight irritation.

Inhalation: May cause irritation of respiratory tract. Ingestion: Ingestion of this product is unlikely.

Chronic Health Effects: There is no known chronic health effect connected with long-term use or contact

May cause slight skin irritation.

Loosefill Insulation Product Code: 23118-NAM Revision:: 08/12/2010 Page:1 of 6

with this product.

This product contains a component which is listed by IARC, OSHA or NTP. See Carcinogenicity:

Section 11 for additional information.

Potential Environmental Effects: There is no known ecological information for this material.

Target Organs: Not available.

Aggravation of Pre-Existing

Chronic respiratory or skin conditions may temporarily worsen from exposure to Conditions:

this product.

OSHA Regulatory Status: This product is considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

#### SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes.

Ensure adequate flushing of the eyes by separating the eyelids with fingers.

Do not rub or scratch eyes.

If eye irritation persists, consult a specialist.

Skin Contact: Wash off immediately with soap and cold water.

DO NOT use warm water because this will open up the pores of the skin, which

will cause further penetration of the fibers. Use a wash cloth to help remove fibers. DO NOT rub or scratch affected areas. Remove contaminated clothing.

If irritation persists get medical attention.

Never use compressed air to remove fibers from the skin.

If fibers are seen penetrating from the skin, the fibers can be removed by applying and removing adhesive tape so that the fibers adhere to the tape and

are pulled out of the skin.

Inhalation: Move to fresh air.

If symptoms persist, call a physician.

Ingestion: Accidental ingestion of this material is unlikely.

If this does occur, watch person for several days to make sure intestinal

blockage does not occur.

Rinse mouth with water and drink water to remove fibers from the throat.

If symptoms persist, call a physician.

Note to Physicians: Treat symptomatically.

# SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties: Non Flammable. Flash Point: Does not apply. Auto Ignition Temperature: Does not apply. Extinguishing Media: dry chemical

foam

carbon dioxide (CO2)

water foo

Wear self-contained breathing apparatus (SCBA) and full fire fighting protective Protective Equipment:

Hazardous Combustion Byproducts:

Carbon monoxide.

Carbon dioxide. Other undetermined compounds could be released in small quantities.

Universal Fire And Explosion

Hazards:

Not available.

# NFPA Ratings:

NFPA Health: NFPA Flammability: 0 NFPA Reactivity: 0

NFPA Other:

# SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Avoid contact with skin and eyes.

**Environmental Precautions:** Prevent further leakage or spillage if safe to do so.

This material will settle out of the air. Methods for containment:

Prevent from spreading by covering, diking or other means.

Loosefill Insulation Product Code: 23118-NAM Revision:: 08/12/2010

Page:2 of 6

Methods for cleanup: Use an industrial vacuum cleaner with a high efficiency filter to clean up dust

and fiber contamination. Avoid dry sweeping.

Pick up and transfer to properly labeled containers.

Other Precautions: Does not apply.

# SECTION 7 - HANDLING and STORAGE

Handling: A void dust formation.

Do not breathe dust.

Wear personal protective equipment.

Storage: Keep product in its packaging until use to minimize potential dust generation.

Product should be kept dry and undercover.

Hygiene Practices: Wash hands before breaks and immediately after handling the product.

Remove and wash contaminated clothing before re-use.

# SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Provide local exhaust and/or general ventilation to maintain exposure below

regulatory and recommended limits.

Dust collection system must be used in transferring operations, cutting or machining or other dust generating processes, such as using power tools.

Vacuum or wet clean-up methods should be used.

Eve/Face Protection: Safety glasses with side-shields.

Skin Protection Description: Protective gloves.

Long sleeved shirt and long pants.

Respiratory Protection: When workers are facing airborne particulate/dust concentrations above the

exposure limit they must use appropriate certified respirators.

A properly fitted NIOSH approved disposable N 95 type dust respirator or

better is recommended.

General Hygiene Considerations: Wash hands before breaks and immediately after handling the product.

Remove and wash contaminated clothing before re-use.

# EXPOSURE GUIDELINES

Ingredient	Guideline OSHA	Guideline NIOSH	Guideline ACGIH	Ontario Canada	Mexico
Fiber Glass (Wool)	PEL-TWA: 1 f/cc (Respirable)		TLV-TWA: 1 f/cc (Respirable)	TWAEV-TWA: 0.05 mg/m3 or 1 f/cc STEL: 0.6 mg/m3	TWA: 0.15 mg/m3
Petroleum distillates, solvent-refined heavy paraffinic	PEL-TWA: 5 mg/m3 (Oil mist)	REL-TWA: 5 mg/m3 (Oil mist)	TLV-TWA: 5 mg/m3 (Oil mist)		

# SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Fibrous. Color: Pink Odor: Odorless Boiling Point: No Data Melting Point: No Data Specific Gravity: No Data

Solubility: Insoluble in water.

Vapor Density: No Data Vapor Pressure: No Data Evaporation Rate: No Data pH: No Data Viscosity: Not applicable.

Flash Point: Does not apply. Auto Ignition Temperature: Does not apply.

# SECTION 10 - STABILITY and REACTIVITY

Loosefill Insulation Product Code: 23118-NAM

Revision:: 08/12/2010 Page:3 of 6 Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to Avoid: None expected

Incompatible Materials: No materials to be especially mentioned.

Special Decomposition Products: See Section 5 of MSDS for hazardous decomposition products during a fire.

#### SECTION 11 - TOXICOLOGICAL INFORMATION

#### Applies to Product :

Acute Toxicity: Dusts may cause mechanical irritation to eyes and skin. Ingestion may cause

 $transient\ irritation\ of\ throat,\ stomach\ and\ gastrointestinal\ tract.\ Inhalation\ may\ cause\ coughing,\ nose\ and\ throat\ irritation,\ and\ sneezing.\ High\ exposures\ may$ 

cause difficulty breathing, congestion, and chest tightness.

Carcinogens:						
	ACGIH	NIOSH	OSHA	IARC	NTP	MEXICO
Fiber Glass (Wool)	A3 Animal Carcinogen	No Data	No Data	Group 3 - Not Classifiable as to its Carcinogenicity to Humans.	RAC - Reasonably anticipated to be a human carcinogen.	A3 Animal Carcinogen
Petroleum distillates, solvent-refined heavy paraffinic	No Data	No Data	No Data	No Data	No Data	No Data

#### Applies to Product:

Sensitization: No information available.

Mutagenicity: No information available.

Reproductive Toxicity: No information available.

Teratogenicity: No information available.

Neurological Effects: No information available.

#### Fiber Glass (Wool):

Chronic Effects: In October 2001, the International Agency for Research on Cancer (IARC)

classified fiber glass wool as Group 3, not classifiable as to its carcinogenicity to humans". The 2001 decision was based on human studies and animal research that have not shown an association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease. This classification replaces the IARC finding in 1987 of a Group B designation

"possibly carcinogenic to humans.".

In May 1997, the American Conference of Governmental Industrial Hygienists (ACGIH) adopted an A3 carcinogen classification for glass wool fibers. The ACGIH A3 classification considers glass wool to be carcinogenic in experimental animals at relatively high doses, by routes of administration, at sites, or by mechanisms that it does not consider relevant to worker exposure. It also reviewed the available epidemiological studies and concluded that they do not confirm an increased risk of cancer in exposed humans. Overall, the ACGIH found that the available medical/scientific evidence suggests that glass wool is not likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure.

In 1994, the National Toxicology Program (NTP) classified glass wool (respirable size) as ""reasonably anticipated to be a human carcinogen"". This classification was primarily based upon the 1987 IARC classification. NTP is currently considering reclassifying this material.

# SECTION 12 - ECOLOGICAL INFORMATION

## Applies to Product:

Ecotoxicity: This material is not expected to cause harm to animals, plants or fish.

Bioaccumulation: Not available.

Biodegradation: Not available.

Mobility In Environmental Media: Not available.

# SECTION 13 - DISPOSAL CONSIDERATIONS

### Applies to Product:

Waste Disposal: Dispose of in accordance with Local, State, Federal and Provincial regulations.

Loosefill Insulation Product Code: 23118-NAM
Revision:: 08/12/2010 Page:4 of 6

Contaminated Packaging: Empty containers should be taken for local recycling, recovery or waste

disposal.

RCRA Number: No EPA Waste Numbers are applicable for this product's components.

RCRA Characteristics: This material is not expected to be a characteristic hazardous waste under

RCRA.

# SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name: Not Regulated. IATA Shipping Name: Not Regulated. Canadian Shipping Name: Not Regulated. IMDG Shipping Name: Not Regulated. ADR Shipping Name: Not Regulated.  ${\sf RID} \; {\sf Shipping} \; {\sf Name} :$ Not Regulated. ICAO Shipping Name: Not Regulated. MEX Shipping Name: Not Regulated.

# SECTION 15 - REGULATORY INFORMATION

**Inventory Status** 

inventory Status	Japan ENCS	EINECS Number	Philippines PICCS	China	South Korea KECL
Fiber Glass (Wool)	Not listed	266-046-0	Listed	Listed	KE-17630
Petroleum distillates, solvent-refined heavy		265-090-8			KE-12614
paraffinic					

	Australia AICS	Canada DSL	TSCA Inventory Status	
Fiber Glass (Wool)	Listed	Listed	Listed	
Petroleum distillates, solvent-refined heavy	Listed	Listed	Listed	
paraffinic				

# Applies to Product:

Canada Reg. Status: This product has been classified in accordance with the hazard criteria of the

Controlled Products Regulations and the MSDS contains all of the information

required by the Controlled Products Regulations.

Canada WHMIS: Not controlled.

CA PROP 65: The following statement(s) are provided under the California Safe Drinking Water

and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the State of California to

cause cancer.

SARA: This product does not contain any chemicals which are subject to the reporting

requirements of the Superfund Amendments and Reauthorization  ${\sf Act}$  of 1986

(SARA) Title III (40CFR, Part 372).

Section 311/312 Hazard

Categories: Acute Health Hazard: yes

Chronic Health Hazard: yes
Risk of ignition: No
Sudden Release of Pressure Hazard: No
Reactive Hazard: No

Clean Air Act: This product does not contain any Hazardous Air Pollutants (HAPs).

State Right To Know

	RI	MN	IL	PA	MA
Fiber Glass (Wool)	Listed	Listed	Listed	Listed	Listed
Petroleum distillates, solvent-refined heavy	No Data				
paraffinic					

	NJ		
Fiber Glass (Wool)	No Data		
Petroleum distillates, solvent-refined heavy	No Data		
paraffinic			

 Loosefill Insulation
 Product Code: 23118-NAM

 Revision: 08/12/2010
 Page:5 of 6

# SECTION 16 - ADDITIONAL INFORMATION

HMIS Fire Hazard: 2\*
HMIS Fire Hazard: 0
HMIS Reactivity: 0
HMIS Personal Protection: X

MSDS Revision Date: August 12, 2010

MSDS Revision Notes: Updated synonym names

Disclaimer: Reasonable care has been taken in the preparation of this information, but the

manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or

consequential damages resulting from its use.

 $\label{lem:copyright} \textbf{Copyright} \\ \textcircled{\onormal} \textbf{1996-2011} \ \textbf{Actio Corporation}. \ \textbf{All Rights Reserved}.$ 

Loosefill Insulation Product Code: 23118-NAM
Revision: 08/12/2010 Page:6 of 6